

AMENDMENTS TO THE SPECIFICATION

Please amend the Specification as follows:

Amend the paragraph on page 7, lines 3-29, as follows:

As mentioned above, full color printing and plotting requires that the colors from the individual cartridges be applied to the media. This causes depletion of ink from the internal cartridge reservoirs. The printer 50 includes four take-a-gulp ink delivery systems (IDSs) to meet the ink delivery demands of the printing system. Each IDS includes three components, an off-carriage ink reservoir, an on-carriage print cartridge, and a print head cleaner. The ink reservoir includes a bag, holding 370 ml of ink for this exemplary embodiment, with a short tube and refill valve attached. Details of a ink reservoir bag structure suitable for the purpose are given in application Ser. No. 08/805,860, SPACE-EFFICIENT ENCLOSURE SHAPE FOR NESTING TOGETHER A PLURALITY OF REPLACEABLE INK SUPPLY BAGS, now U.S. Patent No. 6,030,073, by Erich Coiner et al. These reservoirs are fitted on the left-hand side of the printer (behind the door of the left housing 58) and the valves attach to a valve holder arm 170, also behind the left door, as will be described below. The print cartridge in this exemplary embodiment includes a 300-nozzle, 600 dpi printhead, with an orifice through which it is refilled. The head cleaner (not shown) includes a spittoon for catching ink used when servicing and calibrating the printheads, a wiper used to wipe the face of the printhead, and a cap (used to protect the printhead when it is not in use). These three components together comprise the IDS for a given color and are replaced as a set by the user.